



AIR CONDITIONER

<p>1.EA Type Unit: mm</p>	<p>Operating temp. range</p> <p>Dielectric strength</p> <p>Dissipation constant</p> <p>Thermal time constant</p> <p>Moisture resistance</p>	<p>-20~+105°C</p> <p>1500V AC for one sec</p> <p>MIN. 4 mW/°C</p> <p>MAX.85sec</p> <p>(40°C 95% RH)×1000hours</p>
<p>2.EB Type Unit: mm</p>	<p>Operating temp. range</p> <p>Dielectric strength</p> <p>Dissipation constant</p> <p>Thermal time constant</p> <p>Moisture resistance</p>	<p>-20~+105°C</p> <p>1500V AC for one sec</p> <p>MIN. 5 mW/°C</p> <p>MAX.35sec</p> <p>(40°C 95% RH)×1000hours</p>
<p>3.EC Type Unit: mm</p>	<p>Operating temp. range</p> <p>Dielectric strength</p> <p>Dissipation constant</p> <p>Thermal time constant</p> <p>Moisture resistance</p>	<p>-20~+105°C</p> <p>1500V AC for one sec</p> <p>MIN. 5 mW/°C</p> <p>MAX.85sec</p> <p>(40°C 95% RH)×1000hours</p>
<p>4.ED Type(TSE for old series No.) Unit: mm</p>	<p>Operating temp. range</p> <p>Dielectric strength</p> <p>Dissipation constant</p> <p>Thermal time constant</p> <p>Moisture resistance</p>	<p>-20~+85°C</p> <p>1500V AC for one sec</p> <p>MIN.8 mW/°C</p> <p>MAX.40 sec</p> <p>(60°C 95% RH)×48hours</p>
<p>5.EE Type(TSF for old series No.) Unit: mm</p>	<p>Operating temp. range</p> <p>Dielectric strength</p> <p>Dissipation constant</p> <p>Thermal time constant</p> <p>Moisture resistance</p>	<p>-20~+85°C</p> <p>1500V AC for one sec</p> <p>MIN.8 mW/°C</p> <p>MAX.85 sec</p> <p>(60°C 95% RH)×48hours</p>